



Trailer Model: GTFF402-48

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
48'	8' 6"	48" (Unloaded)	59" (Nominal)	54" (Nominal)	68"	10"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	40" Standard
Side Rails	6" Structural Channel
Crossmembers	4" Jr. I-Beams on 8" Center
Stake Pockets	24" Center, both sides, front & rear, with rubrails
Decking/Flooring	
Main Decking	1 3/8" Apitong Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Tires & Rims	
Tires	11R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Options	
Wide Turn Indicators	
Head Rack, Removable	
Twist locks: 2 for 20' Container, or 1 for 40' container.	
Sliding Winch track road side, and straps both sides.	
Corrugated aluminum side racks, lock in place with J-Locks.	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 NON ABS
Axle 2	Fixed Type 30/30 ABS
Tandem Air Ride Suspension	
2-Speed Landing Gear	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	36"
Swing Clearance	68"
5th Wheel Height	48" (Unloaded)
King Pin	2"

Dealer: