



Trailer Model: GTFV503-53-32

Weight: Apx. \_\_\_\_\_ ± lbs

Overall Length	Overall Width	Gooseneck Length	Deck Height	Load Well Length	Beavertail	Ground Clearance
53'	8' 6"	10'	37"	31' 11"	40"	12"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	40" Standard
Side Rails	Structural Steel Channel
Crossmembers	10" & 4" on 12" Centers
Outriggers	Standard Outriggers
D-Rings	12 each side
Decking/Flooring	
Main Decking	2" Apitong Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Tires & Rims	
Tires	235/75R X 17.5 "H"
Rims	6.75 x 17.5, 8 hole-hub piloted steel
Rear Deck Options	
Beavertail 40"	
Rear Ramps 108" x 36"	
Hydraulic, BI - FOLD	
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	50"
Axle Capacity	25,000lbs
Brakes	12.25" x 7.5" Full Air Brakes with Spring Parking Brakes
ABS	4S3M
Axle 1	Fixed Type 30/30
Axle 2	Fixed Type 30/30 ABS
Axle 3	Fixed Type 30/30 ABS
Air Ride Suspension.	
17" Travel, 2-Speed Landing Gear.	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	18"
Swing Clearance	98"
5th Wheel Height	49"
King Pin	2" Heavy Duty
48" head board w/ center opening	

Dealer: