



Trailer Model: GTFV403-50-30

Weight: Apx. _____ ± lbs

| Overall Length | Overall Width | Gooseneck Length | Lower Deck Length | Lower Deck Height | Ground Clearance |
|----------------|---------------|------------------|-------------------|-------------------|------------------|
| 50' 5" | 8' 6" | 12' 4" | 21' 10" | 36" | 12" |

| Main Deck | |
|-----------------------|--------------------------------------|
| Main Beam | T-1 Steel 16" Fabricated I-Beam |
| Centers | 41" |
| Side Rails | 12" Channels |
| Crossmembers | 10" & 4" |
| Spacing | 12" |
| #Of D-Rings | 9 Ea. Side |
| Concentrated Load | 100,000 lbs in 12' |
| Decking/Flooring | |
| Main Decking | 2" Nominal Apitong |
| Wheel Covers | Steel Covered D-Plate w/grouser bars |
| Rear Deck Options | |
| Bevertail | 40" Steel w/grouser bars |
| Rear Ramps | 136" X 36" Bi-Fold |
| Hydraulic Ramp System | |
| Steel Cleated | |
| Electrical | |
| Lights | LED Plus 2 - Rear Strobes |
| Connector | 7 Way SAE Connector |
| Tires & Rims | |
| Tires | 255/70R x 22.5 "H" |
| Rims | 8.25 x 22.5 Hub Piloted Steel |

| Axles, Suspension, & Running Gear | |
|-----------------------------------|-----------------------|
| # of Axles | 3 |
| Axle Spacing | 49" |
| Axle Capacity | 25,000lbs |
| Brakes | 16 1/2" x 7" - 25K |
| ABS | 4S2M |
| Axle 1 | Fixed Type 30/30 ABS |
| Axle 2 | Fixed Type 30/30 ABS |
| Axle 3 | Fixed Type 30 Non-ABS |
| Spring Ride Suspension | |
| 2-Speed Landing Gear | |
| Gooseneck | |
| King Pin Style | Fixed |
| King Pin Setting | 18" |
| Swing Clearance | 76" |
| 5th Wheel Height | 48" |
| King Pin | 2" Heavy Duty |
| Finish | |
| Sandblast & Powder Coat | |
| Mud Flaps & Reflective Tape | |
| Dealer: | |