



Trailer Model: GTBN352-49-25-GG

Weight: Apx. _____ ± lbs

Overall Length	Overall Width	Gooseneck Length	Lower Deck Length	Lower Deck Height	Rear Deck Length	Rear Deck Height	Ground Clearance
48' 8"	8' 6"	11'	25'	22" loaded	12' 8"	41"	6"

Main Deck	
Main Beam	16" T-1 Steel Std.
Centers	40" Standard
Side Rails	16" T-1 Steel
Crossmembers	10" & 4"
Spacing	12"
# Of D-Rings	13 Each Side
Front Ramps	22"x 41" Paver Ramps
Concentrated Load	70,000 lbs in 12'
Rear Deck	
Riser	3:1 Ratio Wood Filled Full Width
Rear Well Style	Wood Filled Center 1/4" Raised
# of D-Rings	4 Each Side
Decking/Flooring	
Main Decking	1.75" (Apitong - Full Width)
Wheel Covers	Apitong Covered
Well Decking	Apitong
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Hydraulics	
Wet Line Kit - Wing Nut Connection	
13HP - Gas Engine	
Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Outer Aluminium

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	54"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 Non-ABS
Axle 2	Fixed Type 30/30 ABS
Air Ride Suspension - 25K	
Auto Dump	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	16"
Swing Clearance	86"
5th Wheel Height	50"
King Pin	2"
Ride Height	5-Position
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	
Dealer:	