



Trailer Model: GTFF343-40

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
41' 11"	8' 6"	50"	52 1/2" (Unloaded)	52 1/2" (Unloaded)	8' 1"	12"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs.	# of Axles	3
Centers	43 1/2"	Axle Spacing	50"
Side Rails	Structural Channel	Axle Capacity	25,000lbs
Crossmembers	Jr. I-Beams on 12" Center	Brakes	16 1/2" x 7" - 25K
Container Locks	1 for 20' ISO, 2 for 20'ISO, or 1 for 40' ISO container	ABS	4S/2M
Tie-Down	D-links both sides	Axle 1	Fixed Type 30/30 NON ABS
Decking/Flooring		Axle 2	Fixed Type 30/30 ABS
Main Decking	1 3/8" Apitong Flooring	Axle 3	Fixed Type 30/30 ABS
Electrical		Heavy duty tri-axle walking beam suspension system, on/off road	
Lights	LED Plus 2 - Rear Strobes	2-Speed Landing Gear.	
Connector	7 Way Connector	King Pin and Swing Clearance	
Tires & Rims		King Pin Style	Fixed
Tires	11R x 22.5 "H"	King Pin Setting	36"
Rims	8.25 x 22.5 Hub Piloted Steel	Swing Clearance	8' 1"
Finish		5th Wheel Height	50"
Sandblast & Powder Coat		King Pin	2" Heavy Duty
Mud Flaps & Reflective Tape		Dealer:	
Options			
Head Rack, Removable			
Web Winches			
Tie-Down & Sling Provision			