



Trailer Model: GTFF402-48

| Overall Length | Overall Width | 5th Wheel Height | Front Deck Height | Rear Deck Height | Swing Clearance | Ground Clearance |
|----------------|---------------|------------------|-------------------|------------------|-----------------|------------------|
| 48' | 8' 6" | 49" (Unloaded) | 59" | 58" | 74" | 16" |

| Main Deck | |
|---|---|
| Main Beam | 100 KSI flanges and webs. |
| Centers | 44" |
| Side Rails | 6" @ 6.5# Structural Steel Channel |
| Crossmembers | 4" Jr. I-Beams on 12" Centers. |
| Stake Pockets | 24" center, both sides, front & rear, with rubrails |
| Decking/Flooring | |
| Main Decking | 1 3/8" Apitong Flooring |
| Electrical | |
| Lights | LED Plus 2 - Rear Strobes |
| Connector | 7 Way Connector |
| Tires & Rims | |
| Tires | 295/75R x 22.5 "H" |
| Rims | 8.25 x 22.5 Hub Piloted Steel |
| Finish | |
| Sandblast & Powder Coat | |
| Mud Flaps & Reflective Tape | |
| Options Additions | |
| Wide Turn Indicators | |
| Head Rack, Removable | |
| Steel storage box underside of trailer. | |
| Sliding Winch track road side, and straps both sides. | |

| Axles, Suspension, & Running Gear | |
|-----------------------------------|--------------------------|
| # of Axles | 2 |
| Axle Spacing | 49" |
| Axle Capacity | 25,000lbs |
| Brakes | 16 1/2" x 7" - 25K |
| ABS | 2S1M |
| Axle 1 | Fixed Type 30/30 NON ABS |
| Axle 2 | Fixed Type 30/30 ABS |
| Spring ride sliding suspension | |
| 2-Speed Landing Gear. | |
| King Pin and Swing Clearance | |
| King Pin Style | Fixed |
| King Pin Setting | 30" |
| Swing Clearance | 74" |
| 5th Wheel Height | 49" (unloaded) |
| King Pin | 2" Heavy duty |

Dealer: