



Trailer Model: GTF503-32

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
32'	8' 6"	49"	58"	58"	84"	12 1/2"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	44 1/4"
Side Rails	Structural Steel Channel
Crossmembers	Jr. I-Beams on 12" Centers
D Rings	10 each side
Web Winches and rubrails.	
Decking/Flooring	
Main Decking	Steel Smooth Plate, 1/4" Thick Covering The Entire Deck Surface. Allows 4 Tank Locator Brackets Installation
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Tires & Rims	
Tires	11R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Options	
Placard holders & Placard with 8 Panels	
Web Winches	
Toolbox on road side, in the below main deck center.	
4 Swivel hoist rings	

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	54 1/2"
Axle Capacity	25,000lbs
Brakes	16 1/2" X 7" - 25K
ABS	4S2M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Fixed Type 30/30 ABS
Tri-axle spring ride suspension	
Heavy Duty Mark V Series Landing Gear With Sand Shoe And Wheel 10" X 16"	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	20"
Swing Clearance	84"
5th Wheel Height	49"
King Pin	2" Heavy Duty
<b>Dealer:</b>	