



Trailer Model: GTFS402-45-34

Weight: _____ ± lbs

| Overall Length | Overall Width | Gooseneck Length | Deck Height | Load Well Length | Ground Clearance |
|----------------|---------------|------------------|-------------|------------------|------------------|
| 45' | 8' 6" | 10' 10" | 43" LOADED | 34' 2" | 10" |

| Main Deck | | Axles, Suspension, & Running Gear | |
|-----------------------------|--|-----------------------------------|----------------------|
| Main Beam | 100 KSI flanges and webs. | # of Axles | 2 |
| Centers | 42" Standard | Axle Spacing | 49" |
| Side Rails | Structural Steel Channel | Axle Capacity | 25,000lbs |
| Crossmembers | 4 on 12" Centers. | Brakes | 16 1/2" x 7" - 25K |
| Neck | Full Width | ABS | 2S1M |
| Web Winches | 10 each Side | Axle 1 | Fixed Type 30/30 |
| D-Rings | 6 each side | Axle 2 | Fixed Type 30/30 ABS |
| Stake Pockets | 24" center, both sides, front & rear, with rubrails. | Spring Ride Suspension. | |
| Decking/Flooring | | 17" Travel, 2-Speed Landing Gear | |
| Main Decking | 1 3/8" Oak Flooring | Gooseneck | |
| Electrical | | King Pin Style | Fixed |
| Lights | LED Plus 2 - Rear Strobes | King Pin Setting | 16" |
| Connector | 7 Way SAE Connector | Swing Clearance | 92 1/2" |
| Tires & Rims | | 5th Wheel Height | 49 5/8" |
| Tires | 255/70R x 22.5 "H" | King Pin | 2" Heavy Duty |
| Rims | 8.25 x 22.5 10 Hole Hub Piloted Steel | Dealer: | |
| Finish | | | |
| Sandblast & Powder Coat | | | |
| Mud Flaps & Reflective Tape | | | |
| Flag Holders | | | |