



Trailer Model: GTFS22.5 2-43

Weight: \_\_\_\_\_ ± lbs

Overall Length	Overall Width	Gooseneck Length	Swing Clearance	5th Wheel Height	Load Well Length	Front Deck Height	Rear Deck Height
41' 9"	8'	10'	76"	62"	31' 3"	79"	54 5/8"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	42"
Side Rails	Structural Channel Side Rails
Crossmembers	Jr. I-Beams on, evenly spaced Centers.
Tie-Downs	36 "D" ring tie downs on upper and lower deck
D-Rings	18 Per Side
Stake Pockets	Front & Sides
Container locks	8 ISO container locks located on deck, accommodating one (1) 20' ISO in two (2) different locations.
Neck	Full Width, Steel Covered
Decking/Flooring	
Main Decking	1 3/8" (apitong flooring)
Side board kit	25" Front header provided 10" wrap around, side rack panel kit provided, tarp kit provided with bows & securing/fastening items (ropes & straps)
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Options	
	Lockable Tool Box
	Spare Tier & Carrier
	Manifest Box

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	50"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 NON ABS
Spring Ride Suspension. (Single Point Suspension)	
2-Speed Landing Gear.	
Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel
Gooseneck	
King Pin Style	Fixed
King Pin Setting	24"
Swing Clearance	76"
5th Wheel Height	62"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	

Dealer: