



Trailer Model: GTFF402-48

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Ground Clearance	Swing Clearance
48'	8' 6"	48"	59"	54"	14"	68 3/8"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	44" Standard
Side Rails	Structural Steel Channel
Crossmembers	4" Jr. I-Beams on 12" Center
Stake Pockets	24" center, both sides, front & rear, with rubrails
Decking/Flooring	
Main Decking	1 3/8" Apitong
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Tires & Rims	
Tires	11R x 22.5
Rims	8.25 x 22.5 Hub Piloted Steel
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Options	
Wide Turn Indicators	
Head Rack, Removable	
12 Web Winches	
Sliding Winch Track both sides	
Twist locks: 2 for 20' Container, or 1 for 40' container.	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 Non ABS
Axle 2	Fixed Type 30/30 ABS
Air Ride Sliding Suspension	
2-Speed Landing Gear.	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	36"
Swing Clearance	68 3/8"
5th Wheel Height	48"
King Pin	2" Heavy Duty

Dealer: