



Trailer Model: GTFF402-48

Weight: Apx. : 14320 ± lbs

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Ground Clearance	Swing Clearance
48'	8' 6"	48"	59"	54"	14"	68 3/8"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs.	# of Axles	2
Centers	44" Standard	Axle Spacing	49"
Side Rails	Structural Steel Channel	Axle Capacity	25,000lbs
Crossmembers	4" Jr. I-Beams on 12" Center	Brakes	16 1/2" x 7" - 25K
Stake Pockets	24" center, both sides, front & rear, with rubrails	ABS	2S1M
Decking/Flooring		Axle 1	Fixed Type 30/30 Non ABS
Main Decking	1 3/8" Apitong	Axle 2	Fixed Type 30/30 ABS
Electrical		Air Ride Sliding Suspension	
Lights	LED Plus 2 - Rear Strobes	2-Speed Landing Gear.	
Connector	7 Way Connector	King Pin and Swing Clearance	
Tires & Rims		King Pin Style	Fixed
Tires	11R x 22.5	King Pin Setting	36"
Rims	8.25 x 22.5 Hub Piloted Steel	Swing Clearance	68 3/8"
Finish		5th Wheel Height	48"
Sandblast & Powder Coat		King Pin	2" Heavy Duty
Mud Flaps & Reflective Tape		Dealer:	
Options			
Wide Turn Indicators			
Head Rack, Removable			
12 Web Winches			
Sliding Winch Track both sides			
Twist locks: 2 for 20' Container, or 1 for 40' container.			