



Trailer Model: G TSA553-50-38_H

Weight: Apx. : 25560 ± lbs

Overall Length	Lower Deck Length	Axle Space	Overall Width	Lower Deck Height	Ground Clearance
50'	40'	60"	8' 6"	37"	12"

Main Deck	
Main Beam	100,000 PSI Yield
Center	40" apx.
Cross Members	3" JR. I-beam on 8" centers.
Tie Downs	12 D-Rings per side, chain slots
Tool Boxes	Twin Side Mounted in Upper Deck with Lockable Doors
Decking	1 3/8 Apitong
Load Angle : 6.5°	
Dump Angle : 15°	
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Additional Options	
Hydraulic Winch 20K lbs	
Head Rack 48"	
Halogen work lamps	
Full function remote control for Hydraulic and Air functions	
25 HP back up Pony Motor	
Aluminium Outer Rims	
Tires & Rims	
Tires	235/75R X 17.5 "H"
Rims	6.75 X 17.5 Hub Piloted Outer Aluminum

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	60"
Axle Capacity	25,000lbs
Brakes	12 1/4" x 7 1/2" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 Non-ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Fixed Type 30/30 ABS
Air Ride Suspension w/Dump Valve	
Two Speed Landing Gear	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	21"
5th Wheel Height	48"
King Pin	2"
Swing Clearance	80"
Finish	
Sandblast & Powder Coat	
Hydraulics	
Wet line to truck with quick couplers.	
Dealer:	