



**Trailer Model: GTFF402-49**

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
45'	8' 6"	48" (Unloaded)	59" (Nominal)	54" (Nominal)	99"	14"

Main Deck	
Main Beam	Fabricated I-Beam w/pipe bracing running from bottom of sills to main beams
Centers	41"
Side Rails	6" Structural channel @ 6.5 lbs/ft. 5/16" Thick
Crossmembers	4" Jr. I Beams on 8" Centers
D Rings	10 Each Side
Decking/Flooring	
Main Decking	1 3/8" Apitong shiplap flooring secured to frame with floor screws
Electrical	
Lights	LED Plus 2 - Rear Stobes
Connector	12-Volt 7 Way Connector
Tires & Rims	
Tires	11R X 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel Disc Wheels
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Options	
Steel removable header rack 48" in height with chain storage, 10" wrap around	
Steel winch track and straps twelve (12) each located on the driver side	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Capacity	25,000lbs
Axle Spacing	49"
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 Non-ABS
Axle 2	Fixed Type 30/30 ABS
Tandem air ride suspension	
Hubodometer on first axle driver side	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	36"
Swing Clearance	99"
5th Wheel Height	59"
King Pin	2" Heavy Duty

**Dealer:**