



Trailer Model: GTFF402-45

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
45'	8' 6"	48" (Unloaded)	59" (Nominal)	54" (Nominal)	99"	14"

Main Deck	
Main Beam	Fabricated I-Beam w/pipe bracing running from bottom of sills to Main Beams
Centers	44" Standard
Side Rails	6" Structural Channel @6.5 lbs/ft, 5/16" Thick
Crossmembers	4" Jr. I Beams on 8" Centers
Stake Pockets	1 5/8" x 3 1/2" x 1/4" stake pockets, 24" on center, 3/8" x 2 1/2" rub rail w/reflective tape, sides, front and rear double pipe spools.
Decking/Flooring	
Main Decking	1 3/8" Apitong Shiplap Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	12-Volt Electrical System w/7 Way Connector
Tires & Rims	
Tires	11R X 22.5 "H" Load Range, 16 Ply
Rims	8.25 x 22.5 Hub Piloted Steel Disc Wheels
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Options	
Steel removable header rack 48" in height with chain storage, 10" wrap around	
Tool Box under Deck Driver Side	
Steel side racks with 6; panels. Lock in place with J-lock, 42" tall and 48" in Length.	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Capacity	25,000lbs
Axle Spacing	49"
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 Non-ABS
Spring ride suspension, Auto slack adjuster	
2-Speed landing gear	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	36"
Swing Clearance	86"
5th Wheel Height	48"
King Pin	2" Heavy Duty, 3/8" Plate

Dealer: