



Trailer Model: GTFS503-42-32

Overall Length	Overall Width	Gooseneck Length	Lower Deck Length	Lower Deck Height	Swing Clearance	Ground Clearance	Rear Deck Height
42'	8' 6"	10' 10"	32'	40"	84"	9"	40"

Main Deck	
Main Beam	100 KSI flanges and webs
Centers	42" Standard
Side Rails	Structural steel channel
Crossmembers	Jr. I Beams on 12" Center
D-Rings	14 Per Side
Winches & Webbing	Fourteen (14) – seven per side winches, with Rub rails, winch bar and winch straps.
Decking/Flooring	
Main & Gooseneck	Steel smooth plate, ¼" thick covering the entire deck surface. Allows for welding of four tank locator brackets.
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	
Options	
Aluminum Placard holders with Panels	
Tool Box, left (drivers) side of the trailer in front of the rear tires.	
Storage Box on Gooseneck	

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	54"
Axle Capacity	25,000lbs
Brakes	16 ½" x 7" - 25K
ABS	4S2M
Axle 1	Fixed Type 30/30 NON ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Fixed Type 30/30 ABS
Tri-Axle Spring Ride Suspension	
Heavy Duty Mark V Series Landing Gear With Sand Shoe And Wheel 10" X 16"	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	20"
Swing Clearance	84"
King Pin	2" Heavy Duty
5th Wheel Height	49"

Dealer: