



**Trailer Model: GTFF402-48**

**Weight: Apx. : 17490 ± lbs**

| Overall Length | Overall Width | 5th Wheel Height | Front Deck Height | Rear Deck Height | Ground Clearance |
|----------------|---------------|------------------|-------------------|------------------|------------------|
| 48'            | 8' 6"         | 52" (Unloaded)   | 63" (Nominal)     | 59" (Nominal)    | 10 1/2"          |

| Main Deck   |  |
|---|--|
| Main Beam   | 100 KSI flanges and webs.                              |
| Centers   | 44" Standard   |
| Side Rails  | 6" Channel   |
| Crossmembers  | 4" Jr. I-Beams   |
| Spacing   | 12"  |
| Stake Pockets   | 24" center, both sides, 5 front & rear, with rubrails. |
| Decking/Flooring  |  |
| Main Decking  | 1 3/8" Apatong 2 Fasteners per Board                   |
| Electrical  |  |
| Lights  | LED Plus 2 - Rear Strobes                              |
| Connector   | 7 Way SAE Connector                                    |
| Tires & Rims  |  |
| Tires   | 11R x 22.5 "H"   |
| Rims  | 8.25 x 22.5 10 Hole Hub Piloted Steel                  |
| Options   |  |
| Wide Turn Indicators  |  |
| Head Rack, Hubometer, Tool Box  |  |
| Web Winches 12 with straps driver side                                    |  |
| 2 Twist Locks each Side for 20' Container, Rear Impact Guard, Rear Bumper |  |

| Axles, Suspension, & Running Gear           |                      |
|---|----------------------|
| # of Axles                                  | 2                    |
| Axle Spacing                                | 49"                  |
| Axle Capacity                               | 25,000lbs            |
| Brakes                                      | 16 1/2" x 7" - 25K   |
| ABS   | 2S1M                 |
| Axle 1                                      | Fixed Type 30/30 ABS |
| Axle 2                                      | Fixed Type 30/30     |
| Air Ride Sliding Suspension (28' Tuck Axle) |                      |
| 2-Speed Landing Gear                        |                      |
| King Pin and Swing Clearance                |                      |
| King Pin Style                              | Fixed                |
| King Pin Setting                            | 30"                  |
| Swing Clearance                             | 128"                 |
| 5th Wheel Height                            | 52"                  |
| King Pin                                    | 2" Heavy Duty        |
| Finish                                      |                      |
| Sandblast & Powder Coat                     |                      |
| Mud Flaps & Reflective Tape                 |                      |

**Dealer:**