



Trailer Model: GTFF402-48

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
48'	8' 6"	48" (Unloaded)	59" (Nominal)	59" (Nominal)	74"	14"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs.	# of Axles	2
Centers	44" Standard	Axle Spacing	49"
Side Rails	6" Structural Channel	Axle Capacity	25,000lbs
Crossmembers	4" Jr. I-Beams on 8" Center	Brakes	16 1/2" x 7" - 25K
Stake Pockets	24" center, both sides, front & rear, with rubrails with double pipe spools	ABS	2S1M
Decking/Flooring		Axle 1	Fixed Type 30/30 NON ABS
Main Decking	1 3/8" Apitong Shiplap Flooring	Axle 2	Fixed Type 30/30 ABS
Electrical		Tandem air ride sliding suspension.	
Lights	LED Plus 2 - Rear Strokes	2-Speed Landing Gear.	
Connector	7 Way Connector	King Pin and Swing Clearance	
Tires & Rims		King Pin Style	Fixed
Tires	11R x 22.5 "H"	King Pin Setting	36"
Rims	8.25 x 22.5 Hole Hub Piloted Steel	Swing Clearance	74"
Finish		5th Wheel Height	48"
Sandblast & Powder Coat		King Pin	2" Heavy Duty
Mud Flaps & Reflective Tape		Dealer:	
Options			
Twist locks set up for two - 20' Containers & one - 40' Container.			
Steel removable header rack 48" in height with chain storage.			
Sliding Winch track road side, and straps both sides.			
Mudflaps			