



Trailer Model: GTFF402-40

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
45'	8'6"	47" (Unloaded)	59" (Nominal)	54" (Nominal)	99"	14"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	Fabricated I-Beam	# of Axles	2
Centers	44" Standard	Axle Spacing	49"
Side Rails	6" Structural Channel	Axle Capacity	25,000lbs
Crossmembers	4" Jr. I Beams on 8" Centers	Brakes	16 1/2" x 7" - 25K
Stake Pockets	1 5/8" x 3 1/2" x 1/4" stake pockets, 24" on center, 3/8" x 2 1/2" rub rail	ABS	2S1M
Decking/Flooring		Axle 1	Fixed Type 30/30 Non ABS
Main Decking	1 3/8" Apitong Shiplap Flooring	Axle 2	Fixed Type 30/30 ABS
Electrical		Tandem air ride suspension, auto slack adjuster	
Lights	LED Plus 2 - Rear Strobes	2-Speed Landing Gear	
Connector	12-Volt Electrical System w/7 Way Connector	King Pin and Swing Clearance	
Tires & Rims		King Pin Style	Fixed
Tires	11R X 22.5 "H" Load Range, 16 Ply	King Pin Setting	36"
Rims	8.25 x 22.5 Hub Piloted Steel	Swing Clearance	99"
Finish		5th Wheel Height	47"
Sandblast & Powder Coat		King Pin	2" Heavy Duty
Mud Flaps & Reflective Tape		<b>Dealer:</b>	
Options			
Side racks with 6' pane			
Steel removable header rack 48" in height with chain storage, 10" wrap around.			
Sliding Winch track road side, Winch & strap 12 Total loose in box			