



**Trailer Model: GTFF402-49**

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
45'	8' 6"	48" (Unloaded)	59" (Nominal)	54" (Nominal)	99"	14"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	Fabricated I-Beam w/pipe bracing running from bottom of sills to main beams	# of Axles	2
Centers	41"	Axle Capacity	25,000lbs
Side Rails	6" Structural channel @ 6.5 lbs/ft. 5/16" Thick	Axle Spacing	49"
Crossmembers	4" Jr. I Beams on 8" Centers	Brakes	16 1/2" x 7" - 25K
D Rings	10 Each Side	ABS	2S1M
<b>Decking/Flooring</b>		Axle 1	Fixed Type 30/30 Non-ABS
Main Decking	1 3/8" Apitong shiplap flooring secured to frame with floor screws	Axle 2	Fixed Type 30/30 ABS
<b>Electrical</b>		Tandem air ride suspension	
Lights	LED Plus 2 - Rear Stobes	Hubodometer on first axle driver side	
Connector	12-Volt 7 Way Connector	<b>King Pin and Swing Clearance</b>	
<b>Tires &amp; Rims</b>		King Pin Style	Fixed
Tires	11R X 22.5 "H"	King Pin Setting	36"
Rims	8.25 x 22.5 Hub Piloted Steel Disc Wheels	Swing Clearance	99"
<b>Finish</b>		5th Wheel Height	48"
Sandblast & Powder Coat		King Pin	2" Heavy Duty
Mud Flaps & Reflective Tape		<b>Dealer:</b>	
<b>Options</b>			
Steel removable header rack 48" in height with chain storage, 10" wrap around			
Steel winch track and straps twelve (12) each located on the driver side			