



DLA Contract
SPE8EC-D-13-0022




GSA Contract
GS-30F-0027R



DROP DECK, 40 TON

40DP129260



DROP DECK, 40 TON

2 AXLE, MAXIMUM PAYLOAD 80,000 LBS



HIGH QUALITY STEEL

NuStrength™
HIGH PERFORMANCE STEEL

NuStrength™ HR100

HIGH PERFORMANCE STEEL

ULTRA HIGH STRENGTH SHEET
100 KSI / 700 MPA SHEET STEEL COMPARISON

Melted and Manufactured in the USA

Constructed with T-1 100K PSI yield strength Steel. The High Tensile Steel ensures the designed camber is retained, and allows for a longer product service life.

STEMCO WHEEL WARRANTY



5 year wheel end warranty. Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.

COLOR OPTIONS



Globe Trailers can powder coat to the color of your choice

LOCKABLE TOOL BOX



Optional Lockable Tool Box Mounted Underside of Main Deck, 24" x 24" x 48" Steel, curb side.

WEB WINCHES



Web winches are welded on, located on the road side. Used to retain loads and objects on the trailer.

REAR BUMPER



DOT certified rear under ride bumper with high visibility reflective tape and rubber docking bumpers.

WHEEL OPTIONS



All Globe trailers come with standard HUB piloted disc wheels. Wheels are also available in all Aluminum or Outer Aluminum.

RUB RAIL



2 1/2" rolled formed steel. 6" Structural Channel @ 6.5 lbs/ft, 5/16" Thick Stake Pockets 1 5/8" x 3 1/2" x 1/4", 24" O/C, 1/4" x 3" Rub rail.

DECKING OPTIONS



Oak: Standard.
Apitong: Best strength to weight ratios of natural woods.
Rubmer: Composite which is impervious to fluids, mud, oil and UV rays.

LIGHTING SYSTEM



All Lighting is LED and mounted in rubber grommets to DOT standards.

SUSPENSION



Heavy Duty tandem suspension.

COLOR CODED HOSES



Color coded air hoses allow for easy trouble shooting and maintenance.

WIDE TURN SIGNALS



Optional wide turn indicators available.

LANDING GEAR



2 speed Landing Gear, allows for 160,000 lbs static load.


POLYURETHANE VS RUBBER BUSHING



Reduced Maintenance	Increased Maintenance
Increased Trailer Lifetime	Needs Replacement
Increased Trailer Performance	Reduces Trailer Performance
Weather Resistant	Damaged from Weather



All Globe Trailers are 100% powder coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas fired oven to optimum bonding temperature and applying an electrostatically charged zinc rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a top coat chosen from one of Globe Trailers' 188 color options is applied before once more going back in the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.



Trailer Model: GTFS402-56-45

Overall Length	Overall Width	Gooseneck Length	Lower Deck Length	Lower Deck Height	Ground Clearance
55' 10"	8' 6"	10' 10"	45'	40"	7"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	42"
Side Rails	Structural Steel Channel
Crossmembers	Jr. I-Beams.
Stake Pockets	24" Center, both sides, front & rear, with rubrails
Neck	Full Width

Decking/Flooring	
Main & Gooseneck Decking : 1 3/8" Apitong Flooring	

Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector

Tires & Rims	
Tires	255/70R x 22.5 "H"
Rims	8.25 x 22.5 Hub Piloted Steel

Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	

Options	
Full-length track with sliding winches	
Removable steel headboard	
D Rings (6) each side	
Spare Tier & Carrier	
Underbody mount tool, 1 each side of trailer	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	54"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 NON ABS
Axle 2	Fixed Type 30/30 ABS
Spring Ride Suspension	
2-Speed Landing Gear	

Gooseneck	
King Pin Style	Fixed
King Pin Setting	16"
Swing Clearance	92"
5th Wheel Height	48"
King Pin	2" Heavy Duty

Dealer: