



Trailer Model: GTFF503-32

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
32'	8' 6"	49" (Unloaded)	58" (Nominal)	58" (Nominal)	84"	12"

Main Deck		Axles, Suspension, & Running Gear	
Main Beam	100 KSI flanges and webs	# of Axles	3
Centers	44"	Axle Capacity	25,000lbs
Side Rails	Structural steel channel	Axle Spacing	54 1/2"
Crossmembers	Jr. I Beams on 12" Centers	Brakes	16 1/2" x 7" - 25K
D Rings	10 Each Side	ABS	4S2M
Decking/Flooring		Axle 1	Fixed Type 30/30 ABS
Main Decking	Steel smooth plate, 1/4" Thick covering the entire deck surface. Allows 4 Tank locator brackets installation.	Axle 2	Fixed Type 30/30 ABS
Electrical		Axle 3	Fixed Type 30/30 ABS
Lights	LED Plus 2 - Rear Strobes	Tri-Axle spring ride suspension	
Connector	7 Way Connector	Heavy duty mark V Series Landing Gear with Sand shoe and Wheels 10"x16"	
Tires & Rims		King Pin and Swing Clearance	
Tires	11R X 22.5 "H"	King Pin Style	Fixed
Rims	8.25 x 22.5 Hub Piloted Steel	King Pin Setting	20"
Finish		Swing Clearance	84"
Sandblast & Powder Coat		5th Wheel Height	49"
Mud Flaps & Reflective Tape		King Pin	2" Heavy Duty
Options		Dealer:	
Placard holders & placard with 8 panels			
Web winches			
Toolbox on road side, in the below main deck center. 4 swivel hoist rings			