



Trailer Model: GTFF402-48

Weight: Apx. : 14320 ± lbs

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
48'	8'6"	48" loaded	59"	54"	104"	14"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	44" Standard
Side Rails	6" Channel
Crossmembers	4" Jr. I-Beams
Stake Pockets	24" center, both sides, front & rear, with rubrails
Decking/Flooring	
Main Decking	1 3/8" Apitong
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Tires & Rims	
Tires	11R/75R x 22.5 "H"
Rims	8.25 x 22.5 Hole Hub Piloted Steel
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Options	
Wide Turn Indicators	
12 Web Winches with Straps	
Toolbox, Hubometer 10D Rings each side	
Aluminium Stakes every 4"	

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30
Tandem spring ride suspension.	
2-Speed Landing Gear.	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	30"
Swing Clearance	125"
5th Wheel Height	49"
King Pin	2" Heavy Duty

Dealer: