



**Trailer Model: GTFH402-48-31**

**Weight: Apx. \_\_\_\_\_ ± lbs**

Overall Length	Overall Width	Gooseneck Length	Load well Length	Load well Height	Swing Clearance	5th Wheel Height	Hydraulic Tail
48'	8' 6"	9'	31'	36" (Loaded)	86"	48"	8'

Main Deck	
Main Beam	20" Fabricated I-Beam
Crossmembers	10" on loadwell & 4" on neck & rear deck.
# Of D-Rings	8 per side
Stake Pockets	Front & Sides
Decking/Flooring	
Main Decking	1 3/4" Apitong flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Tires & Rims	
Tires	235/75R X 17.5 "H"
Rims	6.75 X 17.5, 8 hole hub piloted steel rims
Hydraulics	
Wet-line system	
Finish	
	Sandblast & Powder Coat
	Mud Flaps & Reflective Tape
	Flag Holders

Axles, Suspension, & Running Gear	
# of Axles	2
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	12 1/4 X 7 1/2
ABS	4S2M
Axle 1	Fixed Type 30/30
Axle 2	Fixed Type 30/30
Air ride suspension w/dump Valve, 2-Speed landing gear	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	16"
Swing Clearance	86"
5th Wheel Height	48"
King Pin	2" heavy duty
20,000# Winch mounted front center of the upper deck	

**Dealer:**