



Trailer Model: GTFF121-28

Weight: Apx. : _____ ± lbs

Overall Length	Overall Width	5th Wheel Height	Front Deck Height	Rear Deck Height	Swing Clearance	Ground Clearance
28'	8'6"	48" loaded	59"	54"	110 1/4"	14"

Main Deck	
Main Beam	100 KSI flanges and webs.
Centers	36" Standard
Side Rails	6" Channel
Crossmembers	4" Jr. I-Beams on 8" Centers
Stake Pockets	24" center, both sides, front & rear, with rubrails rear with doublepipe spools
Decking/Flooring	
Main Decking	1 3/8" Apitong Shiplap Flooring
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way Connector
Tires & Rims	
Tires	295R/75R x 22.5 "H"
Rims	8.25 x 22.5 Hole Piloted Steel
Options	
Steel Removable Header rack 42" in Height	
Removable Stake Bodies All Sides	
Rubber Bumpers on Rear	

Axles, Suspension, & Running Gear	
# of Axles	1
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 ABS
Spring ride suspension.	
2-Speed Landing Gear.	
King Pin and Swing Clearance	
King Pin Style	Fixed
King Pin Setting	30"
Swing Clearance	110 1/4"
5th Wheel Height	48"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	

Dealer: