



Trailer Model: GTFV403-40-27

Weight: Apx. 40,000 ± lbs

Overall Length	Overall Width	Gooseneck Length	Lower Deck Length	Lower Deck Height	Rear Deck Length	Ground Clearance
40'	8' 6"	11' 3"	25'	36"	48"	13 1/2"

Main Deck	
Main Beam	16" Fabricated I-Beam
Centers	36" Standard
Side Rails	16" Fabricated I-Beam
Crossmembers	10" & 4"
Spacing	12"
Outriggers	Removable Standard
# Of D-Rings	12 Each side
Concentrated Load	80,000 lbs
Dual toolboxes in top deck similar to interstate design	
Decking/Flooring	
Main Decking	2" Apitong
Wheel Covers	Steel Covered D-Plate
Electrical	
Lights	LED Plus 2 - Rear Strobes
Connector	7 Way SAE Connector
Tires & Rims	
Tires	Sumitomo ST 727 10R17.5 "H"
Rims	6.75 X 17.5 Hub Piloted Steel
Beavertail & Ramps	
Beavertail 48"	
Toolbox in beaver tail	

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	49"
Axle Capacity	25,000lbs
Brakes	16 1/2" x 7" - 25K
ABS	4S2M
Axle 1	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 ABS
Axle 2	Fixed Type 30/30 NON ABS
Spring Ride Suspension.	
2-Speed Landing Gear	
Gooseneck	
King Pin Style	Fixed
King Pin Setting	18"
Swing Clearance	86" & 93"
5th Wheel Height	50"
King Pin	2" Heavy Duty
Finish	
Sandblast & Powder Coat	
Mud Flaps & Reflective Tape	
Flag Holders	

Dealer: